


Date : 15/10/2015	TECHNICAL DATA SHEET	
Ref. : Peelable mask	<u>PEELABLE MASKING PRODUCT</u>	
Replace 03/04/2014	<u>MSP 75 NEUTRAL</u>	



DESCRIPTION

MSP/75 NEUTRAL is a masking product which can be used when it is necessary to protect from solder. It is therefore extremely useful and advantageous in the soldering of printed circuits on automatic solder machines.

METHOD OF USE

- Apply a thin coat of **MSP/75 NEUTRAL**
- Allow to polymerise at room temperature for approximately 60 mm
- Proceed with soldering (with or without lead)
- When the printed circuit board is cold, peel off the **MSP/75 NEUTRAL**.
In the event of dry oven polymerisation, the temperature should not exceed 60° C for a maximum period of 48 hours.

PACKAGING


- 250 ml plastic bottles

PARTICULARITIES

MSP/75 NEUTRAL is characterised by its pH close to the neutrality. It must be used in every case where the presence of ammoniac is deprecated.

APPLICATION

MSP/75 NEUTRAL represents a simple, rapid and effective manner of masking temporarily and locally areas which are not to be soldered on printed circuits e.g. hardware, inserts, conductors, etc. **MSP/75 NEUTRAL** is easily removed by peeling without leaving any trace after soldering or cleaning.

Date : 15/10/2015	TECHNICAL DATA SHEET	
Ref. : Peelable mask	<u>PEELABLE MASKING PRODUCT</u>	
Replace 03/04/2014	<u>MSP 75 NEUTRAL</u>	

PHYSICAL PROPERTIES

- | | | |
|---------------|------------|--|
| • Colour | Purple | • Solubility in water before polymerisation |
| • Dry extract | 55 - 60 % | • Polymerisation 60 mm (room temperature) according to deposit thickness |
| • Viscosity | 24-28 Pa.s | |
| • pH | 8 – 8,5 | |

SHELF LIFE

6 months

STORAGE

Minimum temperature: 10° C

Maximum temperature: 30° C

We cannot anticipate any and all conditions and situations under which the information and our products or the combination of both with others will be used. We do not assume any liability in the safety and suitability of our products alone or in combination with others. Users must make their own tests to determine the safety and suitability of each product used alone or with other products for their own use. Except any previous written agreement, our products are sold without guarantee and customers must assume all liability for any loss or damage suffered by themselves or by third parties, either from handling or use of our products alone or with others. In case of any difference or variation seen during the use of the products we request that you contact our technical department.